

Product: RTL88x2B USB Software Package - Linux Driver
Version: v5.2.4.1_22719.20170613_COEX20170518-4444

Release History:

v5.1.0-5_18711.20160725_BTCOEX20160707-2100_beta	1. First beta driver
v5.1.6_18923.20160805_BTCOEX20160805-2500_beta	2. Enable TX power by rate 3. Update BTCOEX version 4. Update phydm parameters 5. Update FW 6. Fix concurrent setting 7. Fix TX power limit
v5.1.7_19806.20161025_BTCOEX20161024-3333	1. First normal release. 2. Update PHY parameters to V63 3. Update FW to V8.1 4. Update phydm API 5. Update BTCOEX version to BTCOEX20161024-3333 6. Update HALMAC version to V1_03_02 7. Fix scan DIG issue 8. Fix no rx pkt issue 9. Fix LPS cmd parameter 10. Fix Efues access problem 11. Fix compile error 12. Enable NAPI & GRO
v5.2.4_22552.20170531_COEX20170518-4444	1. Update BTCOEX version to COEX20170518-4444 2. Update phy parameters 3. Update FW to v13.1 4. Support multi port P2P PS 5. Update ChannelPlan document 6. Correct DFS setting 7. Fix compile error in kernel 4.6 & 4.7 8. Fix the mailbox hang problem for COEX 9. Fix system crash due to thread not terminated safely when remove driver 10. Correct register for Wowlan control 11. Fix for power tracking phydm stop 12. Update halmac version to V1_03_09 13. Correct beacon interval setting 14. Fix system hang due to stop xmit thread repeatedly 15. Fix potential memory out of range 16. Support CE-RED. 2G: ETSI v2.1.1 / 5G: ETSI v2.1.0
v5.2.4.1_22719.20170613_COEX20170518-4444	1. Update halmac version to V1_03_09_patch1 to resolve tx fail after resume

	<ul style="list-style-type: none">17. Update parameter to be more tolerance in disconnect decision behavior18. Use driver IQK to let performance more stable
--	---

Realtek

Description:

Realtek provides the solution for WLAN in hardware and software. The software package could be adopted for Realtek RTL88x2B USB WLAN series hardware on Linux based platforms.

Software Version:

RTL88x2B USB Linux Driver Version: v5.2.4.1_22719.20170613_COEX20170518-4444

Software Package Feature:

- IEEE 802.11 b/g/n/ac WiFi compliant
- 802.1x, WEP, WPA TKIP and WPA2 AES/Mixed mode for PSK and TLS (Radius)
- WPS - PIN and PBC Methods
- IEEE 802.11b/g/n/ac Client mode
 - Support wireless security for WEP, WPA TKIP and WPA2 AES PSK
 - Support site survey scan and manual connect
 - Support WPA/WPA2 TLS client
 - Support power saving mode
- Soft AP mode
- WiFi-Direct

Hardware Supported:

- RTL8812BU and RTL8822BU

Platform Supported:

- Linux (kernel 2.6.24 ~ 4.7)
- Android 1.6 ~ 2.3, 4.0 ~ 7.x

CPU supported:

- x86
- ARM
- MIPS